



Cable Ties

 www.elektraefflux.in



- Cable Ties are versatile fastening solution for secure cable management.
- Made from high-quality Nylon PA66 material for resistance to moisture, chemicals, and UV radiation.
- Available in various lengths and strengths for indoor and outdoor applications.



CABLE TIES

ORDERING INFORMATION & TECHNICAL DATA

S No.	CODE	Dimension			Models		SIZE	QUANTITY			STRAPPING RANGE		TENSION	
		L/mm	W/mm	T/mm	MM		Inch	Pcs Bag	Poly/Bag	Total	MM	Inch	LBS	KGS
1	10018	100	1.80	0.95	100	1.80	4"	1000	90	90000	2.0-22	0.08-0.87	16	7
2	10020	100	2.00	0.95	100	2.00	4"	1000	90	90000	2.0-22	0.08-0.87	16	7
3	10022	100	2.20	1.00	100	2.20	4"	1000	90	90000	2.0-23	0.08-0.87	18	8
4	10025	100	2.50	1.00	100	2.50	4"	1000	60	60000	2.0-24	0.08-0.87	18	8
5	11620	100	2.00	1.00	116	2.00	4.60"	1000	50	50000	2.0-25	0.08-0.87	18	8
6	15020	116	2.00	0.97	150	2.00	6"	100	400	40000	2.0-35	0.08-1.38	40	18
7	15027	150	2.70	1.05	150	2.70	6"	100	400	40000	2.0-40	0.08-1.57	40	18
8	15036	150	3.60	1.20	150	3.60	6"	100	200	20000	2.0-41	0.08-1.57	45	20
9	20025	200	2.50	1.10	200	2.50	8"	100	250	25000	3.0-35	0.08-1.57	35	10
10	20028	200	2.80	1.10	200	2.80	8"	400	250	25000	3.0-35	0.08-1.38	40	18
11	20036	200	3.60	1.25	200	3.60	8"	100	200	20000	3.0-42	0.12-1.65	44	20
12	20048	200	4.80	1.28	200	4.80	8"	100	200	20000	3.0-42	0.12-1.65	50	24
13	25029	250	2.90	1.20	250	2.90	10"	100	200	20000	3.0-65	0.12-2.65	44	20
14	25033	250	3.30	1.25	250	3.30	10"	100	150	15000	3.0-65	0.12-2.65	44	20
15	25036	250	3.60	1.25	250	3.60	10"	100	150	15000	3.0-65	0.12-2.65	44	20
16	25048	250	4.80	1.28	250	4.80	10"	100	150	15000	3.0-65	0.12-2.65	50	24
17	30029	300	2.90	1.20	300	2.90	12"	400	200	20000	3.0-70	0.12-2.76	43	19
18	30031	300	3.40	1.25	300	3.10	12"	400	150	15000	3.0-70	0.12-2.76	50	23
19	30037	300	3.70	1.40	300	3.70	12"	100	150	15000	3.0-70	0.12-2.76	50	23
20	30048	300	4.80	1.28	300	4.80	12"	400	100	10000	3.0-70	0.12-2.76	60	28
21	30076	300	7.60	1.50	300	7.60	12°	100	60	6000	3.0-70	0.12-2.76	70	32
22	35039	350	3.90	1.40	350	3.90	14°	400	120	12000	3.0-90	0.12-3.54	55	25
23	35048	350	4.80	1.40	350	4.80	14°	100	100	10000	3.0-90	0.12-3.54	55	25
24	37076	370	7.60	1.45	370	7.60	14.56"	100	40	4000	3.0-100	0.12-3.75	75	34
25	40041	400	4.10	1.40	400	4.10	16"	100	100	10000	5.0-115	0.2-4.52	77	35
26	46051	460	5.10	1.50	460	5.10	18°	400	50	5000	5.0-150	0.2-6.00	88	40

