



PVC Marking Sleeves / Ferruling Tubes



www.elektraefflux.in



- **Material:** Made from premium Heavy Metals free ROHS compliant PVC compound developed in-house by EE.
- Widely used for Printing Markers on all types of Ferrule printing of reputed makes
- Unique round profile for customized cable and wire marking.
- Reduces marking costs in projects for frequent, fast and late stage alterations.
- Fast to use bulk reel and box format.



PVC MARKING SLEEVES/ FERRULING TUBES

Product Code	Inner Diameter (in mm)	Wall Thickness (in mm)	Standard Packing (mtr per roll)	Suitable for wire size
EE - 4001	2.20	0.35	100	0.5 sq. mm
EE - 4002	2.50	0.35	100	0.5 - 0.75 sq. mm
EE - 4003	3.00	0.40	100	1.0 - 1.5 sq. mm
EE - 4004	3.20	0.40	100	1.0 - 1.5 sq. mm
EE - 4005	3.50	0.45	100	2.5 sq. mm
EE - 4006	4.00	0.45	100	2.5 - 4.0 sq. mm
EE - 4007	4.20	0.45	100	4 sq. mm
EE - 4008	4.50	0.45	100	4 sq. mm
EE - 4009	4.70	0.45	100	5 sq. mm
EE - 4010	5.00	0.45	100	4.0 - 6.0 sq. mm
EE - 4011	5.20	0.45	100	6 sq. mm
EE - 4012	5.50	0.50	100	6 sq. mm
EE - 4013	6.00	0.50	100	6.0 - 10.0 sq. mm
EE - 4014	6.30	0.50	100	6.0 - 10.0 sq. mm
EE - 4015	6.50	0.50	100	10.0 sq. mm
EE - 4016	7.00	0.50	100	10.0 sq. mm
EE - 4017	8.00	0.50	100	16.0 sq. mm
EE - 4018	9.00	0.50	100	16.0 sq. mm
EE - 4019	10.00	0.50	100	25.0 sq. mm
EE - 4020	11.00	0.60	100	25 - 35 sq. mm
EE - 4021	12.00	0.60	100	35 sq. mm

Standard Colors: White & Yellow

Other sizes of different inner diameters, wall thickness & colors are available on request.

Available in different packing's like polybag, corrugated reel & corrugated box.

Performance of Marker Tube

Ultimate Elongation: 275 %

Tensile Strength: 15.50 N/mm²

Temperature Range: -20 Deg C to +85 Deg C

Durability: Flammability resistance according to UL94-VO.